


# BRILLIANCE

## SEALER/FINISH



### BENEFITS:

- Reduces Scuffing on Flooring
- Extended Wear Life
- Ultra High Gloss Levels
- Fast drying and extremely durable
- Leaves a deep, clear finish
- Non yellowing- resists discolouration
- Excellent leveling properties

BRILLIANCE has been reformulated with improved scuff resistance and even higher gloss levels. You will see an improvement in the durability and wear life of the floor. New & Improved BRILLIANCE now leads the world in high gloss hard floor finishes.

BRILLIANCE is excellent for use on hard floor surfaces including: terrazzo, vinyl tiles, granite, vinyl sheeting, tiles and slate. BRILLIANCE can be used as a one step sealer finish which gives contractors a simple system that is easy to maintain. BRILLIANCE provides excellent gloss and outstanding depth.

Ground breaking research into modified acrylic copolymers has lead to the development of BRILLIANCE, a product which eliminates the need for a sealer and a finish therefore reducing time and costs as well as simplifying stock control. BRILLIANCE also has excellent leveling characteristics allowing for an even finish with minimal effort.

BRILLIANCE Sealer/Finish is a new generation high gloss polish which provides an amazing “wet look” finish for most modern surfaces. BRILLIANCE is ultra-fast drying and receives a class F slip resistant classification when tested to the requirements of AS/NZS 4586:2004

For Vinyl BRILLIANCE offers a one step Sealer/Finish with amazing results that does not require a base coat.

For terrazzo and stone which often have varying compositions and require a tough base coat, use Impact Base Seal followed by BRILLIANCE.

### DIRECTIONS FOR USE:

#### STRIP

Remove all old polish and sealer using Xpoly8 Floor Stripper ensuring to follow all procedures and directions as per label. Pick up all remaining residue and rinse area with a solution of Tempo HD at a dilution 9mL/Litre of water. After the stripped surface is dry and has been swept the surface is now ready to seal.

Brilliance - January 2013, 1

## SEAL

Apply first coat of BRILLIANCE using a clean applicator, allow 15-30 minutes drying time between coats. (This may vary depending on airflow and drying conditions.) Apply a further 3 coats of BRILLIANCE ensuring each additional coat is laid on a dry surface. If using IMPACT as a base for BRILLIANCE, apply 2-3 coats of IMPACT followed by 2-3 coats of BRILLIANCE. Buff after applying BRILLIANCE.

## CUTBACK AND RECOAT

Sweep area to be cutback. Mix a solution of TEMPO HD at a dilution 17mL/Litre of water, using an autoscrubber fitted with blue or black pads depending on condition of floor. Lay TEMPO HD diluted solution onto floor and allow to work for no more than 4 to 5 minute. Pick up all solution with a second pass of the autoscrubber and complete a total rinse of the surface with clean water ensuring all residue is gone.

When dry, buff the surface to enhance durability and gloss, sweep floor to remove all dust. Apply 2-3 coats of BRILLIANCE using a clean polish applicator. Ensure each coat is dry to touch before you lay the next coat. If time permits always buff last coat after it is dry to assist with curing, this will also enhance gloss and durability.

## MAINTENANCE:

DAILY: Sweep floor

ALTERNATE DAYS:

- Mop and scrub floor with Tempo HD at a dilution of 9mL/Litre of water & buff. (4-5 days/week)
- Use Glokleen or Rejuven8 and buff to provide extra wear and durability to the floor finish as well as increase slip resistance. ( 2-3 days/week)

## SAFETY DATA:

For further information refer to the Material Safety Data Sheet (MSDS) located on the Whiteley Industrial web site: [www.whiteley.com.au](http://www.whiteley.com.au)

## HEALTH AND SAFETY STATEMENT:

There is no way of predicting an individual's response to cleaning or disinfecting products. All cleaning and disinfecting products have potential to cause skin and other irritation in susceptible individuals. Direct physical contact with the skin should be avoided. If irritation does occur when using this product or any other cleaning/disinfecting solution then the individual should be removed from direct contact with the solution until a satisfactory safe working environment for that individual is determined.

Brilliance - January 2013, 2

## **ENVIRONMENTAL STATEMENT:**

Whiteley Industrial manufactures products that comply with Australian and International environmental policy. Whiteley Industrial aims to ensure that every product is 100% biodegradable, whilst achieving optimal performance and benefit to customers. All Whiteley Industrial products are supplied in 100% recyclable containers. Whiteley Industrial and its staff are fully committed to ensuring that our Australian environment and those international environs in which our products are used are enhanced by the use of technology, and that these environments are preserved for the enjoyment of future generations.

© 2013 This document remains property of Whiteley Corporation Pty Ltd. Alterations are not permitted without prior written authorisation from Whiteley Industrial.

Brilliance - January 2013, 3